



1055 Nine North Drive, Alpharetta, GA 30004 USA
 1.800.325.7540 / 770.772.7448 / Fax: 1.888.534.8383
www.demandfoamsystems.com / sales@demandfoamsystems.com



Wall Tac



Available Materials

- High strength nylon

Features/Advantages



- Light to medium loads under dead, variable or vibratory conditions, in solid or hollow environments
- Impervious to moisture
- Quick and easy to install

Concerns

- Drill recommended hole diameter

Installation

- 1 Drill hole slightly deeper than fastener length. Clean hole of debris.
- 2 Tap "Uni-Tap" into place through material to be fastened.



Order Detail

| Order Code | Size | Hole Diameter | | Head Diameter | Grip Range | Ultimate Tensile in Shear Load in Lbs. | | | | Box Quantity |
|------------|--------------|---------------|------------|---------------|--------------|--|-----------------------|----------------------|------------|--------------|
| | | Masonry | Wood/Metal | | | Tension Hollow Wall | Shear Hollow Material | Tension Cement Block | Head Style | |
| WT1B | 9/32 x 1 | 1/4" | 9/32" | 5/8" | 3/16-1/2" | 130 | 250 | 150 | TRUSS | 6000 |
| WT158B | 9/32 x 1 5/8 | 1/4" | 9/32" | 5/8" | 3/8-1 1/8" | 130 | 253 | 158 | TRUSS | 4000 |
| WB218B | 9/32 x 2 1/8 | 1/4" | 9/32" | 5/8" | 7/8-1 5/8" | 130 | 274 | 154 | TRUSS | 2500 |
| WT258B | 9/32 x 2 5/8 | 1/4" | 9/32" | 5/8" | 1 3/8-2 1/8" | 130 | 238 | 163 | TRUSS | 2000 |
| WT318B | 9/32 x 3 1/8 | 1/4" | 9/32" | 5/8" | 1 7/8-2 5/8" | 130 | 228 | 150 | TRUSS | 1500 |