

SHOKOTE FOAM COATING

SHOKOTE is a non-toxic, water based coating for styrofoam and polystyrene foam, as well as other surfaces. It provides a hard, durable finish that resists chipping and cracking, yet can be sanded smooth or carved to add detailing. SHOKOTE can be used on a wide variety of surfaces including foam, primed wood, concrete block, primed fiberglass, paper maché, muslin and many other materials. SHOKOTE is fully compatible with all paints used either as tints or as surface coatings. SHOKOTE is inherently flame retardant and water resistant.

APPLICATION: Apply by brush, roller, or hopper spray gun depending on the desired finish. The thickness of the coating is determined by the application. When coating over fine details, use successive thin coats to build up a protective layer without obscuring the details. For an extra smooth finish without sanding, smooth the coated surface with a wet sponge just before the SHOKOTE has set completely.

SUGGESTED USE: Excellent for use as a protective coating for all types of foam projects. Especially useful on foam scenery or props that receive physical abuse or need to last for extended tours. It can also be used as a texturing agent that is much more durable than plaster or joint compound.

SURFACE PREPARATION:

- *Foam:* All surfaces should be clean and dry before application.
- *Wood & Plastic:* Prime surface with before applying SHOKOTE.
- For particularly difficult materials, lightly sand surface before applying SHOKOTE.

COMPATIBILITY: SHOKOTE is compatible with all water based coatings and is easily painted or tinted. Tint SHOKOTE using paint or Universal Tints. It is not necessary to prime SHOKOTE before painting.

MIXING: Stir well. Due to the weight of the solids in SHOKOTE settling may occur. Use a power mixing blade for best results.

DILUTION: Use SHOKOTE undiluted for most durable single coat application. SHOKOTE may be diluted with water if desired. Thinner mixtures will flow and level more than an undiluted application and will dry to a thinner coating.

COLOR: Off-white, matte finish.

COVERAGE: Varies with application. Approximately 150 sq. ft per gallon.

FILM THICKNESS: Varies with application. 1/16" - 3/16" per application.

DRY TIME: Varies with thickness of coating. Approximately 2-8 hours. Allow 24 hours for full cure.

CLEAN-UP: Soap and water.

SHELF LIFE: Minimum 24 months.

PACKAGING: 3 1/2 Gallon

CAUTIONS: Do not apply when surface or air temperatures are below 50°F. Keep from freezing. Avoid prolonged contact with skin or breathing of spray. Do not take internally. Use adequate ventilation. KEEP OUT OF REACH OF CHILDREN.

All technical data, recommendations and service are accurate to the best of our knowledge. We assume no responsibility for the results obtained or damage incurred from use by the buyer in whole or in part since method of application and its use is beyond our control.