

MATERIAL SAFETY DATA SHEET

Off-Base EIFS Cleaner

| | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---|---------------------|---|--------------------|------------|---------------------|----------|-------------------|----------|---|-------------|-------------|---------|-----------------|--------|----------|----------|------------|---------|--------|--------|-----------|---------------------|--|
| Manufacturer's Name & Address | DEMAND PRODUCTS, INC. 1055 Nine North Drive Alpharetta, GA 30004 USA 1-800-325-7540 | HMIS Symbol: | <table border="1"> <tr> <td>Health</td> <td>2</td> </tr> <tr> <td>Flammability</td> <td>3</td> </tr> <tr> <td>Reactivity</td> <td>0</td> </tr> </table> | Health | 2 | Flammability | 3 | Reactivity | 0 | <table border="1"> <tr> <td>HMIS</td> <td>NFPA</td> </tr> <tr> <td>Minimal</td> <td>0 Insignificant</td> </tr> <tr> <td>Slight</td> <td>1 Slight</td> </tr> <tr> <td>Moderate</td> <td>2 Moderate</td> </tr> <tr> <td>Serious</td> <td>3 High</td> </tr> <tr> <td>Severe</td> <td>4 Extreme</td> </tr> </table> | HMIS | NFPA | Minimal | 0 Insignificant | Slight | 1 Slight | Moderate | 2 Moderate | Serious | 3 High | Severe | 4 Extreme | NFPA Symbol: | |
| | Health | | | 2 | | | | | | | | | | | | | | | | | | | | |
| Flammability | 3 | | | | | | | | | | | | | | | | | | | | | | | |
| Reactivity | 0 | | | | | | | | | | | | | | | | | | | | | | | |
| HMIS | NFPA | | | | | | | | | | | | | | | | | | | | | | | |
| Minimal | 0 Insignificant | | | | | | | | | | | | | | | | | | | | | | | |
| Slight | 1 Slight | | | | | | | | | | | | | | | | | | | | | | | |
| Moderate | 2 Moderate | | | | | | | | | | | | | | | | | | | | | | | |
| Serious | 3 High | | | | | | | | | | | | | | | | | | | | | | | |
| Severe | 4 Extreme | | | | | | | | | | | | | | | | | | | | | | | |
| Emergency Telephone No. | (770) 433-0210 Mon. - Fri. 8 -5 (800) 255-3924 24 Hours | | | | | | | | | | | | | | | | | | | | | | | |
| Date Prepared: | Feb. 18, 2010 | Prepared By: | Vena Burnell | Supersedes: | 11/03/2009 | | | | | | | | | | | | | | | | | | | |

SECTION 1 - IDENTITY

Common Name: (used on label) Off-Base™ # 2356
(Trade name & Synonyms)

Chemical Name Mixture packaged in pressurized aerosol spray can.

SECTION 2 - HAZARDOUS INGREDIENTS

| Principal Hazardous Component(s) | CAS No. | OSHA PEL | ACGIH TLV | Other Limits |
|---|----------|----------|-----------|----------------|
| *Methylene Chloride Methylene Chloride has been shown to cause cancer in certain laboratory animals. Risk to your health depends on the level and duration of exposure. | 75-09-2 | 25 ppm | 50 ppm | N/A |
| *Methyl Alcohol | 67-56-1 | 200 ppm | 200 ppm | 250 ppm (STEL) |
| 9-Octadecenoic Acid | 112-80-1 | Not Est. | Not Est. | |
| Propane | 74-98-6 | Unknown | 1000 ppm | |
| Butane | 106-97-8 | Unknown | 800 ppm | |

*Section 313 Supplier Notification - Indicates hazardous ingredients which are toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

SECTION 3 - PHYSICAL & CHEMICAL CHARACTERISTICS

| | | | | | |
|----------------------------|-----------|--|------------------------------------|------------------------------------|-----|
| Boiling Point | > 100°F | Specific Gravity (H₂O=1) | 1.17 - 1.27 g/mL | Vapor Pressure (Propellant) | N/A |
| % - VOC | 26.1% | Evaporation Rate (BuAc=1) | > 1.00 | pH | N/A |
| Solubility In Water | Insoluble | Appearance and Odor | Clear liquid with ether-like odor. | | |

SECTION 4 - FIRE & EXPLOSION DATA

| | | | | | | |
|--|---|--|-----------|-----------|---------------------------|-------------------------------------|
| Flammability (per flame projection) | Flammable | Flammable Limits in Air (Propellants) | Lower N/A | Upper N/A | Extinguisher Media | Foam, Dry Chemical, CO ₂ |
| Special Fire Fighting Procedures | Keep containers cool using water spray. Use proper equipment to protect personnel from bursting containers. | | | | | |
| Unusual Fire and Explosion Hazards | Contents under pressure. Do not expose to temperatures exceeding 120° F as containers may vent, rupture or burst. | | | | | |

SECTION 5 - PHYSICAL HAZARDS

| | | | | | |
|---|---|----------------------------|--------------------------------|---------------------------------|--|
| Stability | Unstable <input type="checkbox"/> Stable <input checked="" type="checkbox"/> | Conditions to Avoid | Open Flames; Temp. > 120°F. | Hazardous Polymerization | May Occur <input type="checkbox"/> Will not Occur <input checked="" type="checkbox"/> |
| Incompatibility (Materials to Avoid) | Strong oxidizers. | | | | |
| Hazardous Decomposition Products | CO, CO ₂ | | | | |

SECTION 6 - HEALTH HAZARDS

| | | | | |
|--|--|--|--|---|
| Routes of Entry | Inhalation: Yes | Eyes / Skin: Yes | Ingestion: Unlikely | |
| Signs and Symptoms of Exposure (Acute & Chronic) | EYES: Vapor can irritate eyes. May cause pain and irritation with mild temporary damage. INHALATION: May cause central nervous system depression. May cause headache, dizziness, stupor and loss of consciousness. In confined areas, respiratory irritation may occur; INGESTION: If vomiting occurs, can be aspirated into the lungs which can cause chemical pneumonia and systemic effects. May cause abdominal pain, malaise, central nervous system effects. SKIN: Can cause irritation, de-fatting and dermatitis of skin. Single exposure can result in progressively severe burning sensation and redness. May be absorbed through the skin and cause adverse health effects. | | | |
| Medical Conditions Generally Aggravated by Exposure | Organ (heart, lung, kidney) and skin conditions | | | |
| Chemical Listed as Carcinogen or Potential Carcinogen | NTP | Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> | I.A.R.C. 2B Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> | OSHA Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> |
| Emergency and First Aid Procedures | | | | |
| 1. Inhalation | Move to fresh air. If breathing has stopped, administer artificial respiration. Contact physician or emergency facility immediately. | | | |
| 2. Eyes | Flush eyes with water for at least 15 minutes. Get medical attention if irritation persists. | | | |
| 3. Skin | Remove contaminated clothing and shoes. Wash exposed area thoroughly with soap and water for at least 15 minutes. Wash contaminated clothing before reuse. | | | |
| 4. Ingestion | Do not induce vomiting. Get medical attention immediately. | | | |
| Note to Physician | Chlorinated hydrocarbons may sensitize the heart to epinephrine. | | | |

SECTION 7 – SPECIAL PROTECTION INFORMATION

| | | | | | | | | |
|---|---|--------------------------------|-----------------------------|----------------|----------------|-----|--------------|-----|
| Respiratory Protection (Specify Type) | Air – supplied respirator should be used in confined areas. | | | | | | | |
| Ventilation | Local Exhaust | Maintain adequate ventilation. | Mechanical (General) | N/A | Special | N/A | Other | N/A |
| Protective Gloves | Viton | | Eye Protection | Safety Glasses | | | | |
| Other Protective Clothing or Equipment | Impervious clothing. Wash hands after use. | | | | | | | |

SECTION 8 – SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

| | |
|---|---|
| Precautions to be Taken Handling and Storage | WARNING: FLAMMABLE. Vapor Harmful. Contents under pressure. Use only in a well ventilated area. Avoid breathing vapor or mist. Avoid contact with eyes. Do not smoke while using. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid prolonged contact with skin. Do not store at temperatures above 120°F. Do not puncture or incinerate containers. Keep out of reach of children. Store in a cool, dry, well ventilated area away from incompatible materials. Store in accordance with NFPA 30B for Level 3 Aerosols. |
|---|---|

| | |
|--------------------------|--|
| Other Precautions | Read label precautions carefully. Follow label directions to avoid injury. |
|--------------------------|--|

| | |
|--|---|
| Steps to be Taken in Case Material is Released or Spilled | Soak up spilled liquid with absorbent material. Place in closed metal drum for proper disposal. |
|--|---|

| | |
|-------------------------------|--|
| Waste Disposal Methods | Dispose of in accordance with local, state, and federal regulations. Wrap container in newspaper and place in trash. |
|-------------------------------|--|

| | |
|-----------------------|--|
| Proposition 65 | California Safe Drinking Water and Toxic Enforcement Act of 1986 WARNING: This product may contain a chemical(s) known to the State of California to cause cancer. |
|-----------------------|--|

| | |
|----------------------------|---|
| Transportation Info | DOT CLASSIFICATION: HAZARDOUS PACKING GROUP: N/A DESCRIPTION: CONSUMER COMMODITY, ORM-D UN NUMBER: UN 1950 HAZARD CLASS: 2.1 |
|----------------------------|---|

We believe all information given is accurate. It is offered in good faith, but without guarantee. Since conditions are beyond our control, user assumes all responsibility and risk.

1002356 / 9042356 090311



1055 Nine North Drive / Alpharetta, GA 30004 USA
1-800-325-7540 / Fax 1-888-534-8383
www.demandproducts.com