

RAINTEK™ Universal Kickout

Material Safety Data Sheet

Section 1 • IDENTIFIERS

Product Name: Raintek™ Universal Kickout
MSDS #: 816-0000-0001-1
Date: 8/01/11
Flammability Hazard: 1 – Slight
TSCA Registry: CAS# 9003-07-0
This product should not be considered hazardous material.

Section 2 • PHYSICAL & CHEMICAL CHARACTERISTICS

% Volatile, Vol.: < 0.4
Freezing/
Melting Point: 160°C, 320°F
Solubility
in Water: Negligible
Specific
Gravity: 0.88 – 0.92

Section 3 • FIRE, EXPLOSION, REACTIVITY HAZARD DATA

Flash
Point: > 329°C, 625°F
Autoignition
Temperatures: > 329°C, 625°F
Extinguishing
Media: Water spray, dry chemical, foam, or carbon dioxide.
Fire-Fighting
Procedures: Standard procedures for Class A fires.
Stability: Stable.
Incompatibility: Avoid contact with strong oxidizing agents.
Hazardous
Products of
Combustion: Carbon dioxide, carbon monoxide.

Section 4 • HEALTH HAZARD DATA Molten Resins

If molten material comes in contact with the skin, cool under a running stream of water. Do not attempt to remove the resin from the skin. Removal could result in severe tissue damage. Get medical attention.

Section 5 • SPILL AND LEAK

PROCEDURES

Released
or Spilled: Sweep up spilled material for use or disposal.
Waste
Disposal: Incineration of waste material in a permitted facility in accordance to local, state, and federal regulations is the recommended disposal method.
Landfilling in a licensed facility in accordance to local, state, and federal regulations is a suitable alternative.
This product is not listed in federal hazardous waste regulations
40 CFR 261.33 paragraphs (e) or (f), i.e., chemical products that are considered hazardous if they become wastes. It does not exhibit any of the hazardous characteristics listed in 40 CFR 26) Subpart C. State or local hazardous waste regulations may apply if different from the federal.

Section 6 • APPLICABLE CONTROL MEASURES

Protective
Equipment: Safety glasses.
Work
Practices: Eyewash fountains and safety showers should be easily accessible.
Handling &
Storage: Keep away from sparks and open flame.
This product may react with strong oxidizing agents and should not be stored near such materials.
Keep temperature below 60°C, 140°F, for quality control.
Engineering
Controls: Provide adequate ventilation.
Extruder should be properly vented.
Protective

Measures: Eliminate ignition sources.
We cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety of our products, either alone or in combination with other products. Users are advised to make their own tests to determine the safety and suitability of each such product or product combination for their own purposes.