

DEMAND

PRODUCTS INC
ROUTERS • HOTWIRE • FASTWIRE • EIFS

FOAM LOK ADHESIVE Water Based Material Safety Data Sheet

FOAM LOK ADHESIVE

Water Based

Material Safety Data Sheet

Date of Preparation: 10.12.99

Revised: 03.24.2007

DISTRIBUTED BY:

Demand Products, Inc.
1055 Nine North Drive, Alpharetta, Ga 30004 USA
Telephone: 1-800-325-7540

24-hour Emergency:
Chemtrec 1-800-424-9300

HMIS:

Health:	1
Reactivity:	0
Flammability:	0
Personal Protection Equipment:	B

Product Identification:
Product Number: 1212
Product Class: Latex Adhesive
Product Name: Water Based Contact Cement
Trade Name: CASA 1212B-PT

HAZARD INGREDIENTS: Ammonia

PHYSICAL DATE:

Boiling Point:	212° F
Vapor Density:	Heavier than air.
Evaporation Rate:	Same as water.
Appearance and Odor:	Blue Milky latex Slight Ammonia
Specific Gravity:	0.97
Percent Volatile by Volume:	30-40%
Solubility in Water:	Soluble
V.O.C. (calculated)	"0" grams/liter

FIRE & EXPLOSION FIRE HAZARD DATA:

Flammable Limits:	No flashing
Flash Point:	N. D.
Flammability Classification:	OSHA: None DOT: None
Extinguishing Media:	CO2, chemical foam, water fog.
Special Fire Fighting Features:	Wear self-contained breathing gear when in confined area.

HEALTH HAZARD DATA:

Threshold Limit Value:	None
Effects of Overexposure:	None

EMERGENCY & FIRST AID EMERGENCY DATA:

Keep out of eyes. Flush with water for 10-15 minutes. If irritation persists, consult a physician. May cause slight irritation of the skin. Wash with soap and water. If swallowed, consult a physician.

REACTIVITY DATE:

Conditions to avoid: Excessive heat or cold.
Stability: Stable.
Incompatibility: None known.
Hazardous Decomposition Products: Normal (CO2, CO)
Hazardous Polymerization: Will not occur.

SPILL OR LEAK PROCEDURE:

Ventilation:	Local ventilation
Protective Gloves:	Recommended
Eye Protection:	Recommended
Hygienic Practices:	Wash with soap and water after exposure.
Respiratory Protection:	Not required
Other Protective Equipment:	None

SPECIAL PRECAUTIONS/OTHER COMMENTS

Precautions to be taken in handling and storing:
Store inside at a temperature of 60° F to 100° F.
Do not allow product to freeze.
Other precautions: None
Propellant: UN1066 Non-flammable
Compressed Gas 2.2

TRANSPORTATION DATA:

D.O.T. Hazard Class: 2.2
Shipments exceeding 1000 lbs. must be placarded.